

QuickView 4MP

Vandalproof PTZ camera with intelligent control



CAMERA	
Image sensor	1/1,8" progressive CMOS
Sensitivity	Day / Night / LED - 0,002 Lux / 0,0002 Lux / 0 Lux
Shutter time	1/1 s - 1/30 000 s
AGC	Auto / Manual
Day/Night mode	True
Digital zoom	16x
Focus mode	Auto / Semi-auto / Manual
Intelligent image quality correction	3D digital noise reduction Backlight compensation Bright light compensation Digital WDR Digital image processing (mist-, smog-, smoke filter) Digital image stabilization
LENS	
Focal length	5.7 mm - 205.2 mm, 36× optical zoom
Zoom speed	4,4 s
Focus	Auto / Semi-auto / Manual
Angel of view	Horizontal: 51.1°-1.7° Vertical: 31.3°-1.0°
PTZ PROPERTIES	
Movement range (Pan)	360° (endless)
Movement speed (Pan)	0.1°/s - 210°/s (configurable), Preset speed: 280°/s
Movement range (Tilt)	-20° to 90°
Movement speed (Tilt)	0.1°/s - 150°/s (configurable), Preset speed 250°/s
Presets	300
Intelligent control	Auto turn by clicking on the live image Auto turn and zoom by selected area on the live image
IMAGE	
Max. resolution	2560 × 1440
Frame rate	50Hz:25fps (2560 × 1440, 2048 × 1536, 1920 × 1080, 1280 x 960, 1280 x 720, 704 x 576, 640 x 480, 352 x 288) 60Hz: 30fps (2560 × 1440, 2048 × 1536, 1920 × 1080, 1280 x 960, 1280 x 720, 704 x 480, 640 x 480, 352 x 240)
IR ILLUMINATION	
IR illumination distance	200 m
Smart IR	support
COMPRESSION	
Video compression	H.265 / H.264 / MJPEG
Audio compression	G.711alaw / G.711ulaw / G.722.1 / G.726 / MP2L2 / PCM
SYSTEM INTEGRATION	
Network interface	RJ45 10M/100M Ethernet interface; Hi-PoE
Audio	1 channel audio input and 1 channel audio output
Alarm	7 channel alarm input and 2 channel alarm output
Server independent storage	Built-in memory card slot, support Micro SD/SDHC/SDXC
NETWORK	
Klient software	Intellio Video System 4
Web browser	IE 8 - 11, Chrome 31.0 - 44, Firefox 30.0 - 51
INTELLIGENT VIDEO	
Smart tracking	Automatic tracking of moving objects
Onboard detectors	Tripwire and entry detection



QuickView 4MP

Vandalproof PTZ camera with intelligent control



GENERAL

Working temperature	-40°C to 70°C
Power	24 VAC (Max. 60 W) Hi-PoE (Max. 50 W)
Protection level	IP67, IK10, TVS 6000V, lightning -, surge - and voltage transient protection
Dimensions	Φ 266.6 mm x 410 mm
Weight	8000 g

DIMENSIONS

