



EINAR

Traffic Monitoring Cameras

Smart Parking Made Simple

Einar is a fully automated plug-n-play camera with optional onboard ANPR and superior imaging. Its sleek design, super easy setup, and user-friendly interface make it ideal for any smart parking, slow traffic monitoring, and vehicle access projects.

Easy Installation and Operation

Preconfigured settings for direct ANPR and access control or slow traffic monitoring. IP-based remote access for convenient operation.

Powered with PoE+

Supplied by Power over Ethernet+ technology and GPIO connectivity, Einar allows for a simple single-cable connection.

User GPIO-port

Factory-supported GPIO-port for direct communication with universal controllers. This means no intermediary device is needed for opening and closing gates and barriers.

Models

ANPR

	Einar 5 (Standard)	Einar 5T (Telelens)	Einar 5W (White Illumination)
ANPR at 0 Lux	1.5 m – 4 m	4 m – 8 m	1.5 m – 4 m
Maximum ANPR range at optimal conditions	20 m	35 m	20 m
Maximum recommended vehicle speed		70 km/h*	

Imaging

Resolution (HxV pixels) @ framerate	2592 x 1944 @ 60 FPS		
Lens & zoom (all auto and motorized)	3 – 12 mm, 4x	9 – 22 mm, 2x	3 – 12 mm, 4x
Shutter	Rolling shutter		

Illumination

Wavelength	850 nm (infrared)	White
Illumination modes	Continuous	

Processing & I/O

CPU for ANPR	1.25 GHz + HW accelerator
Communication protocols	NTP, TCP/IPv4, DHCP, DNS

Electrical Data

Power requirement	PoE+
Power consumption typical	5 W
Connectivity	PoE+ (RJ45) & GPIO
SD-card slot	User accessible

On-board Intelligence

Carmen® ANPR	Optional
Video analytics	Vehicle detection, tracking, intelligent motion detection, alarms
Color + Make and Model Recognition (MMR)	-
Trigger sources	In-built video analytics

Mechanical Data

Internal operating temperature	30°C – +85°C
IP rating	IP67
Dimensions (without bracket) (LxWxH)	167 x 126 x 100 mm
Weight (without bracket)	1.2 kg
In the box	Camera, shield, bracket, IP67 RJ45 connectors (cables not included)

Optional Accessories

Various brackets for different mounting solutions (i.e. hidden cables, pole mounting, wall mounting, ceiling mounting)

* Recommended maximum vehicle speed may be lower

Contact

ADAPTIVE RECOGNITION

www.adaptiverecognition.com



Check Product Details

Request information

Adaptive Recognition global offices



Adaptive Recognition **America**



Adaptive Recognition **Nordic**



Adaptive Recognition **Hungary**



Adaptive Recognition **Singapore**

Disclaimer

The information contained in this brochure is provided as is and without any warranties of any kind, whether expressed or implied, including but not limited to, implied warranties of satisfactory quality, fitness for a particular purpose and/or correctness. The contents of this brochure is for general information purposes only and do not constitute advice. Adaptive Recognition does not represent or warrant that the information and/or specifications contained in this brochure are accurate, complete or current and specifically stipulate that certain scanner details and specifications contained in this brochure may differ in available models. Therefore, Adaptive Recognition makes no warranties or representations regarding the use of the content, details, specifications or information contained in this brochure in terms of their correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise, in each case to the fullest extent permitted by law.